



## **Canyon Creek – LVP Glue Down**

### **Installation, Warranty, and Care & Maintenance Instructions**

#### **INSTALLATION INSTRUCTIONS:**

##### **Suitable Surfaces**

Dry, clean, well-cured concrete, APA rated ¾" tongue and groove plywood or APA rated ¾" tongue and groove OSB subfloors, are suitable. All surfaces must be dry, clean and free of substances that may prevent adhesive bonding. Some surfaces may require application of a sealer before applying adhesive. Old adhesive residue must be properly prepared with embossing leveler. Existing wood plank floors must be covered with 6.35 mm (0.25") minimum or thicker APA rated underlay panels. Over crawl spaces, all wood floors must be suspended at least 457.2 mm (18") above the ground for ventilation.

##### **Unsuitable Surfaces**

Surfaces that are susceptible to moisture damage, such as particleboard, chipboard, or OSB sheathing. Pressure treated or coated plywood, carpet, or cushioned underlay. Rough, heavily textured and/or uneven surfaces may telegraph through the vinyl and distort the finished surface. Installation of a plywood underlayment or embossing leveler will be necessary in these areas.

**WARNING: DO NOT REMOVE OLD RESILIENT FLOORING. THESE PRODUCTS MAY CONTAIN EITHER ASBESTOS FIBERS OR CRYSTALLINE SILICA, WHICH CAN BE HARMFUL TO YOUR HEALTH.**

#### **RADIANT HEATED FLOORS**

Can be installed over hydronic or electric radiant heat systems under the following conditions:

- The heat system must be operational and run for a minimum of 2 weeks prior to the installation.
- Use a full spread, permanent adhesive following the manufacturer's directions.
- The temperature of the system should be set at 18°C(65°F) three days before installation and should be gradually increased in daily increments of 2°C (5°F) to reach the desired temperature.
- The maximum floor surface temperature must not exceed 29°C (84°F).
- There must be a minimum of 12 mm (1/2") between the heating system and the flooring product.
- All radiant heat floor manufacturer's instructions must be properly followed.
- Electric heat cables or mats must be encapsulated in a cementitious leveling compound or thin-set mortar that meets the moisture level and pH requirements listed above.
- Electric heat systems should have separate sensors and temperature controls in each room.

## Preparation

The vinyl planks should be allowed to acclimatize at room temperature (18–29° C/65–84° F) for 48 hours prior to installation. Carefully check planks for any defects before installation. Check that all ITEM NUMBERS are the same and that you have purchased sufficient material to complete the job.

New concrete floors need to dry out for at least 60 days prior to installation. All concrete slabs must be checked for moisture before installing product. Moisture emissions from the subfloor cannot exceed 3.6 kg per 93 m<sup>2</sup> (8 lbs per 1000 ft<sup>2</sup>) per 24 hours, as measured with the calcium chloride test in accordance with the latest edition of ASTM F1869. Internal relative humidity must be tested in accordance with the latest edition of ASTM F2170. Humidity should not exceed 85%. Be sure to also observe the adhesive manufacturer's requirements. On or below grade concrete slabs must have an effective vapor barrier installed directly under the slabs. Excessive moisture in the subfloor could promote mold, mildew and other moisture related issues, which can contribute to an unhealthy indoor environment.

All nail heads must be driven down below the surface. Securely nail all loose boards. Scrape, plane or fill uneven boards, holes or cracks using floor-leveling compound. Make sure the floor is smooth, clean, and free of wax, grease, oil or dust and sealed as necessary before laying Planks. Remove any traces of glue or residue from the previous flooring. Irregularities in the subfloor will show through the finished floor. Any unevenness in the subfloor should be limited to the applicable national standard: a maximum of 3/16" in 10' (5 mm in 3 m) (ASTM E1486) or 1/8" in 6' (3 mm in 2 m) (BS8203).

For ceramic, mosaic, terrazzo and quarry tile floors, fill grout lines with a proper leveling compound.

## GLUE DOWN INSTALLATION

**ADHESIVE:** For areas with radiant-heat floors, rolling traffic (wheelchairs, etc.), high direct sunlight, high moisture (bathrooms, laundry rooms, etc.), or commercial installations, use a high-quality, full-spread, firm-set adhesive. Pressure sensitive adhesive is acceptable for residential areas that are not listed above.

## Planning Your Floor

**If your floor has arrows on the back, make sure you lay them in the same direction according to the arrows.**

Begin in the corner of the longest wall. Use spacers along each wall to maintain an expansion space of 6–8 mm (1/4"–5/16") between the wall and the flooring.

Prior to applying the adhesive, lay a complete row of planks to determine the length of the final plank. If the last plank is shorter than 300 mm (11.8"), then adjust the starting point accordingly; this is necessary in order to achieve the correct staggered effect. **Diagram 1.**

## Laying your floor

Apply adhesive as recommended by your flooring retailer at the corner of the longest wall, using a 1.6 mm (1/16") square notch trowel or as recommended by the adhesive manufacturer. Avoid spreading more adhesive than needed

Most full-spread adhesives require rolling the floor with a 75-100 lb roller after the planks are installed. Check the directions from the adhesive supplier.

Position the first plank at your starting point. Check that this position is correct and apply firm, all over pressure to achieve contact. Lay all planks ensuring a close fit but do not force together. Ensure that the cut edge always faces the wall. We recommend that you stagger the joints a minimum of 300 mm (11.8") apart, but you may stagger them as little as 203.2 mm (8") apart.


### Diagram 2.

To fit air vents, doorframes, etc., make a cardboard pattern as a guide and use this to draw an outline on the plank. Cut to shape and check that it fits. It should fit snugly and should not be forced into place.

Continue installing planks in the same way as described above.

## Final cutting last row

When you reach the last row, you may find that the gap is less than one full plank wide. To ensure accurate cutting of the final row, lay the plank to be cut exactly over the last full plank, lay another full plank against the wall and mark the cutting line where the planks overlay. Before applying the adhesive, check that the cut plank fits correctly. The plank should not be forced into place. **Diagram 3.**



## CARE AND MAINTENANCE:

**Avoid exposure to direct sunlight for prolonged periods of time. Use drapes or blinds to minimize direct sunlight during peak sunlight hours.**

- **Surface temperature should never exceed 29° C (84° F).**
- When you have finished laying your floor, clean up any remaining or spilled adhesive with a damp cloth. Allow 5 to 7 days before cleaning the floor to allow the perimeter planks to adhere to the sub floor.
- If an edge or corner of the flooring happens to lift slightly in specific areas, use double sided floor tape to adhere the floor flush to the subfloor.
- Sweep regularly to remove surface grit and dust. Use a damp cloth or mop to clean up any dirt and footprints. Avoid using excessive amounts of moisture, as this may cause bond failure for the adhesive. All spills should be cleaned up immediately.

**CAUTION:** Planks are slippery when wet.

- Never use wax, polish, abrasive cleaners or scouring agents as they may dull or distort the finish.
- High heels can damage floors.
- Do not allow pets with unclipped nails to scratch or damage the floor.
- Use felt pads under heavy furniture, chairs and tables.
- Caster chairs can damage the floor. It is recommended to use a chair pad or soft castors that are designed for wood floors.
- Use doormats at entrance ways to protect the floor from discoloring. Avoid using rubber-backed rugs, as they may stain or discolor the vinyl flooring. If you have an asphalt driveway, use a heavy-duty doormat at your main door, as chemicals in asphalt can cause vinyl flooring to yellow.
- If you install this product in areas that are exposed to long term direct sunlight, such as sunrooms or solariums, you must use window treatments to block the sunlight during peak sunlight hours.
- It's a good idea to save a few planks in case of accidental damage. Planks can be replaced or repaired by a flooring professional.
- Installation of flooring should begin after the jobsite has been cleaned and cleared of other trades.

**CAUTION:** Some types of nails, such as common steel nails, cement coated or some resin-coated nails, may cause a discoloration of the vinyl floor covering. Use only non-staining fasteners with underlayment panels. The procedure of gluing and screwing underlayment panels is not recommended. Solvent based construction adhesives are known to stain vinyl floor coverings. All responsibility for discoloration problems caused by fastener staining or the use of construction adhesive rests with the underlayment installer/consumer.

## **WARRANTY:**

This guarantee is for replacement or refund of the vinyl plank flooring only, not labor (including the cost of labor for installation of the replacement floor) or costs incurred with loss of time, incidental expenses or any other damage. It does not cover damage from improper installation or maintenance (including side or end gapping), burns, tears, indentations, stains or reduction in gloss level due to normal use and/or exterior applications. Gapping, shrinkage, squeaks, fading, structural sub floor related issues, scratches and scuff marks are not covered under this warranty. **Temperature variations – excessive heat (29° C/84° F) or below freezing (-4° C/25° F and below) – may cause expansion or contraction of the product.**

### **Lifetime Limited Residential Warranty**

Our Lifetime Limited Residential Warranty for vinyl plank means that, for the duration of your life in your home, from the date of purchase, your floor will be free from manufacturing defects and will not wear through or permanently stain from common household stains when installed and maintained according to instructions supplied with each carton. \*Lifetime means 40 years.

### **30-Year Limited Commercial Warranty**

Our 30 Year Limited Commercial Warranty for vinyl plank means that for 30 years, from the date of purchase, your floor will be free from manufacturing defects and will not wear through when installed and maintained according to instructions supplied with each carton. Improper installation or workmanship should be directed to the contractor who installed the floor.

### **Claims**

This guarantee applies only to the original purchaser and proof of purchase is required for all claims. Claims for wear must show a minimum dime size area. This guarantee is pro-rated based on the amount of time the floor has been installed. If you wish to file a claim under warranty, contact the authorized dealer where the flooring was purchased.